



| | |
|--------------------------|--|
| typology | Vegetable tanned bovine saddle-hide |
| thickness | 2.4/2.6 mm |
| height | 750 gr/mtl |
| weight | ~2.000 gr/sqm |
| fire resistance | 1IM, UNI 8456 (1987), UNI 9174 (1987), UNI 9174/A1 (1996), UNI 9177 (1987) |
| washing information | The upholstery is in totally natural, prime quality full grain saddle-hide. It is very sensitive: be careful of liquids or other substances that could alter the colour of the leather, and also of metallic or sharp parts that could leave marks on the surface. |
| cleaning and maintenance | Only use specific leather cleaners. / Avoid direct exposure to sunlight and sources of heat. / Avoid contact between light and dark colours, and between different materials. / Dust with a soft dry cloth. |

Legenda

| | | | |
|--|---|-----|------------------|
| | Hand wash. Delicate wash. Maximum temperature: 30°/40°. Use neutral soap without optical whiteners. | CO | Cotton |
| | Wash at a maximum temperature of 30°. Pay attention to the maximum degrees indicated, they can range from 30° to 95 °. | LI | Linen |
| | Dry clean only. Do not wash in water. Treat with care when damp. | NY | Nylon |
| | Dry clean with tetrachloroethylene, monofluorotrichloromethane, trifluorochloroethane, hydrocarbons. Severely limit the amount of water added and/or the mechanical action and washing and drying temperatures. Do not dry clean at automatic coin-operated laundry facilities. | PA | Polyamide |
| | Dry clean with perchlorethylene | PAN | Polyacrylic |
| | Do not dry clean. | PC | Acrylic |
| | Do not tumble dry. | PES | Polyethersulfone |
| | Tumble dry. | PL | Polyester |
| | Do not centrifugate. | PP | Polypropylene |
| | Iron at low temperature without steam (max 110°C). | PU | Polyurethane |
| | Ironing at moderate temperature (max 150°C). | SE | Silk |
| | Iron on reverse. | VI | Viscose |
| | Do not iron. | WO | Wool |
| | Do not use chlorine bleach. | WV | virgin wool |
| | Wet-cleaning. | | |
| | Dry cleaning with hydrocarbons and trifluoro-trichloroethane. | | |
| | Dry at low temperatures. | | |

Saddle-hide

Variants



R900 col.02

R903 col.03



R904 col.26

R906 col.29



R908 col.15